

Silicon NPN Power Transistors

2SD718

DESCRIPTION

- With TO-3P(I) package
- Complement to type 2SB688

APPLICATIONS

- Power amplifier applications
- Recommend for 45~50W audio frequency amplifier output stage

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter




Fig.1 simplified outline (TO-3P(I)) and symbol

Absolute maximum ratings(Ta=25)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	120	V
V_{CEO}	Collector-emitter voltage	Open base	120	V
V_{EBO}	Emitter-base voltage	Open collector	5	V
I_C	Collector current		8	A
I_B	Base current		0.8	A
P_T	Total power dissipation	$T_C=25$	80	W
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-55~150	

Silicon NPN Power Transistors

2SD718

CHARACTERISTICS

Tj=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Base-emitter breakdown voltage	$I_C=50mA, I_B=0$	120			V
V_{CEsat}	Collector-emitter saturation voltage	$I_C=5A; I_B=0.5A$			2.5	V
V_{BE}	Base-emitter voltage	$I_C=5A; V_{CE}=5V$			1.5	V
I_{CBO}	Collector cut-off current	$V_{CB}=120V; I_E=0$			10	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=5V; I_C=0$			10	μA
h_{FE}	DC current gain	$I_C=1A; V_{CE}=5V$	55		160	
f_T	Transition frequency	$I_C=1A; V_{CE}=5V$		12		MHz
C_{ob}	Output capacitance	$I_E=0; V_{CB}=10V; f=1MHz$		170		pF


◆ h_{FE} Classifications

R	O
55-110	80-160

Silicon NPN Power Transistors

2SD718

PACKAGE OUTLINE



Silicon NPN Power Transistors

2SD718

