

FOR USE BY ELECTRICIANS OVERSEAS :

最新トランジスタ規格表 (New Transistor Manual) lists all the transistors registered with the Electronic Industries Association of Japan (EIAJ), arranged in a manner easy to look up. We hope that you will make full use of the data provided in this manual by referring to the Japanese-English translation key given below.

型名	社名	用途	構造	最大定格 (T _b =25°C)					電気的特性 (T _b =25°C)										備考	
				V _{ceo} (V)	V _{ceo} (V)	I _c (mA)	P _c (mW)	T _j (°C)	I _{ceo} 最大値 (μA)	直流又はパルスI _{BE}		バイアス		h _{FE}	h _{FE} h _{FE} * (Ω)	h _{FE} h _{FE} * (×10 ⁻⁴)	h _{FE} h _{FE} * (μS)	f _{αB} f _r * (Mc)		C _{ob} (pF)
1	2	3	4	5					6		7		8				9	10	11	12

- 1 TYPE NUMBER
- 2 ORIGINAL MANUFACTURER
- 3 USES
- 4 MATERIAL AND STRUCTURE
- 5 MAXIMUM RATINGS
- 6 I_{CBO} MAXIMUM VALUE AND V_{CB} VALUE (CRITERIA FOR MEASURING I_{CBO})
- 7 STANDARD VALUE OF DC/PULSE h_{FE} AND V_{CE}, I_C (CRITERIA FOR MEASURING DC/PULSE h_{FE})
- 8 STANDARD VALUE OF h PARAMETERS AND BIAS V_{CB}, I_E (CRITERIA FOR MEASURING h PARAMETERS)

- * INDICATES VALUE IN GROUNDED-BASE OPERATION, OTHERWISE VALUE IN EMITTER-GROUNDED OPERATION.
 - 9 f_{αB} OF RF CHARACTERISTIC, EXCEPT IN CASE OF * WHICH INDICATES VALUE OF f_r.
 - 10 C_{ob} AND r_{bb'} OF RF CHARACTERISTICS EXCEPT IN CASE OF * IN r_{bb'} COLUMN WHICH INDICATES VALUE OF h_{ie} (real)
 - 11 OUTLINE
 - 12 REMARKS
- :とコンプリ: COMPLEMENTARY TO

